

# RIV506 Hydropneumatic tool for structural blind rivets

**new**

**Code 4692100**

To place structural blind rivets,  
in all materials, Ø 6.4 (Magnariv, Monriv)  
and Gtrriv Ø 7.7.

RIV506 is a hydropneumatic tool with retention of the blind rivet and capture of the separated mandrel. Plastic handle and aluminium body make the tool light and handy, and consequently easy to use for operators. RIV506 combines functionality with a highly competitive price, which makes it very attractive for those who uses this kind of tool continuously and professionally.

## Fittings



Description	Pc	Code
Nosepiece Ø 4.8 mm	1	<b>4169100</b>
Nosepiece Ø 6.4 mm for structural rivets (on head)	1	<b>4724400</b>
Nosepiece Ø 4.8-3/16 mm for Monriv rivet	1	<b>2524800</b>
Nosepiece Ø 6.4-1/4 mm for Monriv rivet	1	<b>4041900</b>
Nosepiece Ø 6.4 mm for Lockriv rivet	1	<b>4173500</b>
Nosepiece Ø 6.4 mm for standard rivets	1	<b>4041700</b>
Nosepiece Ø 6.4 mm for Magnariv rivet	1	<b>4041800</b>
Jaws (3 pcs)	2	<b>4723300</b>
Jaw opener	1	<b>4133900</b>
Jaw return spring	1	<b>4134000</b>
Jaws carrier cone	1	<b>4133800</b>
Oil syringe	1	-
Oil	1	-
Hexagonal allen wrench 3 mm	1	-
10-12 mm wrench	1	-
16-17 mm wrench	2	-

The tool is supplied with kit Ø 6.4 for structural blind rivets already assembled.

## Technical data and features

Air working pressure	<b>6 bar</b>
Min-max air pressure	<b>5/7 bar</b>
Air consumption per cycle (6 bar)	<b>4.8 lt</b>
Stroke	<b>20 mm</b>
Max power (6 bar)	<b>18000 N</b>
Weight	<b>1.866 Kg</b>
Vibrations	<b>&lt; 2,5 m/s<sup>2</sup></b>
Noise level	<b>78.5 dB (A)</b>

## Optional

Picture	Description	Code
	Kit 506 - extension 100 mm	<b>4204300</b>
	Kit 506 - extension 200 mm	<b>4226800</b>

